

FreeSpace FS2C

in-ceiling loudspeaker

Product Overview

FreeSpace FS loudspeakers are designed for high-quality performance in background music and voice announcement applications. Redesigned enclosures and aesthetics, removeable logos, metal backcans on ceiling-mount models, and ease-of-installation features mean that this update to the classic FreeSpace DS line is ideal for installations in almost any commercial space.

The ceiling-mount FS2C features a full-range 2.25-inch cone transducer, low frequency range down to 85 Hz, 16-ohm and 70/100 V operation, with front baffle-mounted tap settings, and front baffle audio connections on a detachable Euroblock connector.



Key Features

High-quality loudspeaker solutions for voice and background music

Updated enclosures and removeable logos that do not leave grille marks or holes

Low-impedance and high-impedance operation without separate model versions

Consistent tonality throughout the line means mixing and matching models in the same installation

UL1480 ULC-S541 Life Safety Fire Alarm and Signaling listed

Black and White versions of all models

Designed for in-ceiling installation with UL2043 plenum rated backcan and front baffle audio wiring access

Compact enclosure design featuring an 18.3 cm (7.2-in) baffle diameter and a metal 12.5 cm (4.9-in) backcan

Technical Specifications

SINGLE LOUDSPEAKER PERFORMANCE		
Frequency Response (-3 dB) ⁽¹⁾	95 - 18,000 Hz	
Frequency Range (-10 dB) ⁽¹⁾	85 - 19,000 Hz	
Nominal Coverage Angle ⁽²⁾	180°	
Nominal Coverage (1 - 10 kHz)	165°	
	Bose extended-lifecycle test ⁽⁵⁾	AES transducer test ⁽⁶⁾
Power Handling, long-term continuous	16 W	20 W
Power Handling, peak	64 W	80 W
Sensitivity (SPL/1W @ 1 m) ⁽³⁾	84 dB	84 dB
Calculated Maximum SPL @ 1 m ⁽⁴⁾	96 dB	97 dB
Calculated Maximum SPL @ 1 m, peak	102 dB	103 dB
Loudspeaker EQ	Not Required, Bose EQ Voicing and SmartBass available	
Recommended High-Pass Protection	85 Hz with minimum 24-dB/octave filter	
Transformer taps	70V: 1, 2, 4, 8, 16 W, bypass 100V: 2, 4, 8, 16 W, bypass	
TRANSDUCERS		
Full-Range Driver	1 x 2.25-inch woofer (57 mm)	
Nominal Impedance	16 ohms (transformer bypass)	

FreeSpace FS2C

in-ceiling loudspeaker

PHYSICAL	
Enclosure Material	Engineered-plastics front baffle with integrated steel formed back can
Grille	Perforated steel, powder-coated finish
Logo	Rotatable, removable
Color	Black: similar to Ral 9005, White: similar to Ral 9003
Environmental	Indoor only
Safety Agency	Certification: UL 1480, ULC-S541 for Fire Alarm and Signaling Systems Installation: NFPA 70, NFPA 72, CSA C22.1 Section 32, in accordance with IEC60268-5, CE RoHS
Operating Temperature Range	0 °C to 50 °C (32 °F to 122 °F)
Connectors	Euro block 6-pin connector with loop-through, front-baffle mounted Accepts 18 AWG (0.8 mm ²) to 14 AWG (2.5 mm ²) size wire
Wire/Conduit Entry	Top and side wire entry point 1/2-inch knockouts allow for 9.5 mm (3/8 in) conduit and fittings
Suspension/Mounting	Two (2) standard mounting arms plus one (1) safety cable tab
Maximum Ceiling Thickness	38 mm (1.5 in)
Product Dimensions (Baffle Diameter × Depth)	183 × 132 mm (7.2 × 5.2 in)
Backcan Dimensions (Diameter × Depth)	155 × 125 mm (6.10 × 4.92 in)
Ceiling Cutout	165 mm (6.5 in)
Net Weight	1.63 kg (3.6 lb)
Shipping Weight, Pair	4.4 kg (9.7 lb)
Included Accessories	Each FS2C includes one (1) cut-out template per box
Optional Accessories	Adjustable Tile-Bridge 6-Pack, DesignMax DM2CRI Rough-in kit 6-pack, Retrofit Kit, Ceramic terminal w/ Fuse kit
PRODUCT CODES	
841154-0110	FREESPACE FS2C PAIR BLK
841154-0210	FREESPACE FS2C PAIR WHT

Footnotes


- (1) Frequency response and range measured on-axis in half-space environment with recommended EQ
- (2) 1 kHz to 4 kHz average
- (3) Sensitivity measured on-axis in half-space environment with recommended EQ
- (4) Maximum SPL calculated from sensitivity and power handling specifications, exclusive of power compression
- (5) Bose extended-lifecycle test using pink noise filtered to meet IEC268-5, 6-dB crest factor, 500-hour duration
- (6) AES standard 2-hour duration with IEC system noise

For additional specifications and application information, please visit PRO.BOSE.COM.
Specifications subject to change without notice. 01/2020


FreeSpace FS2C

in-ceiling loudspeaker


Dimensions





Side View



Front View
GRILLE REMOVED FOR CLARITY



Right View
DIMENSIONS APPLY TO BOTH SIDES



Rear View

For additional specifications and application information, please visit PRO.BOSE.COM. Specifications subject to change without notice. 01/2020